

Light efficiency:

**212 Lumen/Watt**

Light quality:

**CRI: 69.0**

Color temperature:

**5746 K**


**Output: 1039 lm**

**Peak: 786 cd**

**Power: 4.9 W**

**19.6V @ 0.250A**

2 PLANES




Beam angle

**360°**

Color

CIE1931  
x: 0.327  
y: 0.347

Spectra



Product name:

**PIL-HP-WHITE-15D**

Date and time:

**10/12/2020 3:00:40 PM**

Item number:


**PIL-HP-WHITE-15D**

Operator:


**HUNZA**

Additional information:



**PILLAR LIGHT HIGH POWER -  
250MA 19.6 x2 VOLT - IP66 -  
WHITE - 15 DEGREE - SOLID  
POWDERCOATED  
ALUMINIUM**



TM30: 70.5



CRI: 69.0 (R1-R8)



CRI R values, only R1-R8 are used to calculate final CRI value

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
66.96	72.03	75.08	70.93	68.12	62.71	77.77	58.21	-34.11	33.46	68.77	38.87	66.82	85.91	60.41


TM30 C values, 16 binned values out of total of 99 C values

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
66.43	74.07	59.61	64.95	70.69	82.92	83.32	74.28	78.02	60.92	53.60	69.73	79.98	74.92	70.58	74.44

CQS Q values


Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8	Q9	Q10	Q11	Q12	Q13	Q14	Q15
77.83	91.52	60.46	56.98	67.69	69.98	73.67	84.59	88.38	69.63	64.92	67.02	69.86	56.23	65.07

CQS: 69.1



## Color parameters

CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Duv
5746 K	69.0	-34.1	70.5	94.8	69.1	0.3	0.3	0.2	0.3	0.0021



## Intensities in 0° c-plane

0°	9°	18°	27°	36°	45°	54°	63°	72°	81°	90°	99°	108°	117°	126°	135°	144°	153°	162°	171°
786	651	412	242	131	63	31	16	9	3	1	4	9	17	32	66	133	244	416	646
100%	83%	52%	31%	17%	8%	4%	2%	1%	0%	0%	0%	1%	2%	4%	8%	17%	31%	53%	82%

## Intensities in 90° c-plane

0°	9°	18°	27°	36°	45°	54°	63°	72°	81°	90°	99°	108°	117°	126°	135°	144°	153°	162°	171°
786	651	412	242	131	63	31	16	9	3	1	4	9	17	32	66	133	244	416	646
100%	83%	52%	31%	17%	8%	4%	2%	1%	0%	0%	0%	1%	2%	4%	8%	17%	31%	53%	82%

## Intensities in 180° c-plane

0°	9°	18°	27°	36°	45°	54°	63°	72°	81°	90°	99°	108°	117°	126°	135°	144°	153°	162°	171°
786	651	412	242	131	63	31	16	9	3	1	4	9	17	32	66	133	244	416	646
100%	83%	52%	31%	17%	8%	4%	2%	1%	0%	0%	0%	1%	2%	4%	8%	17%	31%	53%	82%

## Intensities in 270° c-plane

0°	9°	18°	27°	36°	45°	54°	63°	72°	81°	90°	99°	108°	117°	126°	135°	144°	153°	162°	171°
786	651	412	242	131	63	31	16	9	3	1	4	9	17	32	66	133	244	416	646
100%	83%	52%	31%	17%	8%	4%	2%	1%	0%	0%	0%	1%	2%	4%	8%	17%	31%	53%	82%

Beam angle 50%	Field angle 10%	Cutoff angle 2.5%	Intensity ratio in 120° cone	Intensity ratio in 90° cone
360.0°	360.0°	360.0°	47.5%	42.9%